605-5130-01 - Data Sheet

21K F.A. Round Bottom Manifold⁽¹⁾ Tank Model/Make: FARBM / Modern

Product Description

This tank has a smooth interior wall and round bottom for easy cleaning.

Technical Data

Weights and Measures

Capacity	500 BBL (21,000 gallons)
Height	10'-8" (grade to roof plate) 13'-4" (grade to upright guardrail)
Width	8'-6"
Length	47'-2" (nose to tail) 42'-11" (end wall to end wall)
Weight	29,000 lbs. (est.)

Structural Design

Floor	1/4" thick ASTM A36 carbon steel round bottom
Sides/Ends	1/4" thick ASTM A36 carbon steel
Top Deck	1/4" thick ASTM A36 carbon steel
Wall Frame	6" wide channel-shaped steel (on exterior side of walls)
Roof Frame	3" wide x 1½" tall channel-shaped steel (on exterior side of roof deck)

Wetted Materials for material compatibility check

Carbon Steel*	Tank walls, bottom, sides; steam coil (if supplied)
Carboline Liner	Tank interior (Could be Phenoline 310 or Phenoline 380 – confirm which)
Buna (Nitrile, NBR)	Manway gaskets, valve seats, P/V valve gasket
Nylon 11	Valve disc
304 Stainless Steel	Float ball

*Theoretically if the tank has an interior liner, no carbon steel should be exposed to the liquid. However, if there are areas of thin or missing liner, bare carbon steel will be exposed. It is always a good idea to check compatibility of carbon steel even if the tank interior is lined.

Strapping Table: ST327



Features

Valves	2-Front &1-Rear: 4"- wafer butterfly valve. Cast iron body, Buna-N seat & seals, 416 SS stem, Nylon 11 coated ductile iron disk w/ plug and chain.
Relief Valve	16 oz./in2 pressure setting, 0.4 oz./in2 vacuum setting; Buna-N seal
Front Inlet	8" connection, flanged on the inside and outside of the tank
Front Drain	4"-150# flanged connection with butterfly valve
Rear Drain	4"-150# flanged connection with butterfly valve and remote operation handle
Fill Line	3" pipe, top of tank, with cap and chain
Gel Line ²	4" sch. 40 pipe; flanged with butterfly valve
Top Vapor	4"-150# weld neck flange with blind flange (<i>chained</i>) and Buna N gasket
Top Manway	One - 211/2" I.D. domed lid w/anti-personnel bars, slotted hinges and 5 - 3/4" T or eye bolt with wing nut fasteners, hinged to side of tank. Buna-N <i>(NBR)</i> gasket.
Front Manway	One - 21½" I.D. domed lid, slotted hinges and 5 - ¾" T or eye bolt with wing nut fasteners, hinged away from stairs. Buna-N (<i>NBR</i>) gasket.
Side Manway	One - 211⁄2" I.D. domed lid, slotted hinges and 5 - ¾" T or eye bolt with wing nut fasten- ers, mounted on passenger side and hinged to front of tank. Buna-N (NBR) gasket.
Stairway	Front-mounted with access from driver's side of tank
Level Gauge	Ball style with 2-8" 304 SS floats. Floor supports hold floats $\frac{1}{2}$ " off floor.
Tires	11.00 x 22.5 (nylon tubeless)
Axles	25K axle, automatic slack adjusters, top mounted 30 service chambers, outboard drums

1 It is possible that the manifold has been removed from the tank. All Data on this data sheet is still valid. 2 It is possible that the gel line has been removed. Check equipment if this item is required for the application being rented for.

Surface Details


Exterior Coating	High gloss polyurethane paint
Interior Lining	Chemical resistant lining
Placard Mounts	Removable 10-gauge steel, 48"x48", both sides of tank at top rear. Secured with nylock nuts or bolts with lock washers.


UnitedRentals.com | 800.UR.RENTS © 2018 United Rentals, Inc.

To the best of our knowledge the technical data contained herein are true and accurate at the date of issuance and are subject to change without prior notice. No guarantee of accuracy is given or implied because variations can and do exist. NO WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY UNITED RENTALS, EITHER EXPRESSED OR IMPLIED.


605-5130-01 - Data Sheet

21K F.A. Round Bottom Manifold⁽¹⁾ Tank Model/Make: FARBM / Modern





REAR VIEW



FRONT VIEW



100 First Stamford Place, Ste 700 Stamford, Ct 06902 | USA

UnitedRentals.com | 800.UR.RENTS © 2018 United Rentals, Inc.

To the best of our knowledge the technical data contained herein are true and accurate at the date of issuance and are subject to change without prior notice. No guarantee of accuracy is given or implied because variations can and do exist. NO WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY UNITED RENTALS, EITHER EXPRESSED OR IMPLIED.